

# TLF-600824

## 1.45kWh

### Battery PACK



- ✓ Longer Usage Life
- ✓ High Power Capacity
- ✓ High Energy Density
- ✓ Environment Friendly
- ✓ Light Weight

## Pack Specification

**Model: TLF-600824**

Item	Specification	Remarks
<b>Electrical</b>		
Module Configuration	19S 4P	-
Installed Energy	1.45 KWh	-
Usable Energy	1.31 KWh	@ 90%
Nominal Voltage	60.8 VDC	-
Operating Voltage Range	52.25 ~ 69.35 VDC	-
Rapid Charge Current	12 A	@ 0.5C
Rated Charge Current	5 A	@ 0.2C
Pulse Discharge Current	50 A	≤ 2S
Rated Discharge Power	1.45 kW	-
Rated Discharge Current	24A	-
BMS Features	Deep discharge & Over Charge, Cell Balancing & temperature compensation, short circuit	-
Communication (If required)	CAN, RS485, UART, BLUETOOTH	-
<b>Mechanical</b>		
Dimension	180 (L) x 165 (B) x 385 (H) mm	±5 mm
Housing Material	MS Casing	
Weight	17 kg	±5%
IP Grade	IP63	-
Cell	32650-3.2V-6000mAh	-
Charge/Discharge Terminal	SB50	-
<b>Environment</b>		
Operating Temperature	Charging	0 ~ 45°C
	Discharging	20 ~ 55°C
Storage Humidity		<60±25% RH
Storage Temperature	1 Year	-20 ~ 25°C
	6 Months	25 ~ 35°C
	3 Months	35 ~ 45°C
	<1 Week	45 ~ 60°C
<b>Expected Cycle &amp; Calendar Life**</b>		
Cycle Life @ DoD 90%	≥2,000 cycles	@ 25±3°C, 0.2C/1C

**\*\*Depending on the load profile, the warranty condition may differ\*\***

**We reserve the right to change the content of specification without prior notice.**